

PP Box Strapping Specification

USE TYPE	Product Polypropylene Box Strapping			Length Average/ Meterage +/- 5%	Average Net Wt (Kgs) +/- 100 gm	Average Strength (+/- 5% Kgs)
	Code	Width (-0.2 to - 0.6 mm)	Thickness (+0.00 to + 0.08 mm)			
Suitable for all high production Fully Automatic power strapping machines Standard Core Sizes- 152 ID X 150 L x 700 gram 203 ID X 188 L x 500 gram 406 ID X 150 L x 2000 gram 386 ID X 155 L x 2000 gram or as required Packing- 1 to 2 rolls in one paper sheet / carton.	550	5	0.50	5000	8.00	40
	560	5	0.60	3000	5.70	50
	560	5	0.60	5000	9.50	50
	660	6	0.60	3000	6.00	60
	660	6	0.60	5000	10.00	60
	840	8	0.40	2000	4.00	60
	860	8	0.60	2000	5.50	75
	960	9	0.60	3000	9.00	80
	960	9	0.60	2000	6.00	80
	970	9	0.70	2000	7.00	90
	1170	11	0.70	2000	8.00	110
	1110	11	1.00	1000	6.00	160
	1260	12	0.60	2000	8.00	110
	1270	12	0.70	2000	9.00	120
	1560	15	0.60	1500	9.00	150
	1560	15	0.60	2000	12.00	150
	1570	15	0.70	1000	7.00	160
	1580	15	0.80	1000	7.50	170
	1590	15	0.90	1000	8.40	180
	1590	15	0.90	1500	12.50	180
1880	18	0.80	1500	11.70	180	
Suitable for all high production Semi Automatic power strapping machines Standard Core Size- 203 ID X 165 L x 450 gram Packing- 1 to 2 rolls in one paper sheet / carton	550	5	0.50	2000	3.20	40
	650	6	0.50	2000	3.50	50
	660	6	0.60	2000	4.00	60
	850	8	0.50	2000	4.50	65
	950	9	0.50	2000	5.00	70
	960	9	0.60	2000	6.00	80
	1140	11	0.40	2000	5.00	70
	1150	11	0.50	2000	6.00	80
	1160	11	0.60	2000	7.00	90
	1170	11	0.70	2000	8.00	110
	1240	12	0.40	2000	6.00	80
	1250	12	0.50	2000	7.00	90
	1260	12	0.60	2000	8.00	110
	1270	12	0.70	2000	9.00	120
	1280	12	0.80	2000	10.50	150
	1550	15	0.50	1000	5.00	140
	1560	15	0.60	1000	6.00	150
	1580	15	0.80	2000	15.00	170
	1950	19	0.50	1000	6.00	160
	1980	19	0.80	1000	9.00	200
Manual Suitable for all hand tools Standard Core Size - - 76 ID X 165 L X 100 gram Packing- 10 rolls in one raffia bag	950	9	0.50	1000	2.50	70
	960	9	0.60	1000	3.00	80
	1140	11	0.40	1000	2.50	70
	1150	11	0.50	1000	3.00	80
	1160	11	0.60	1000	3.50	90
	1240	12	0.40	1000	3.00	80
	1250	12	0.50	1000	3.50	90
	1260	12	0.60	1000	4.00	110
	1280	12	0.80	1000	6.00	150
	1210	12	1.00	1000	7.00	160
	1550	15	0.50	1000	5.00	130
	1560	15	0.60	1000	6.00	150
	1590	15	0.90	1000	8.40	180
	1950	19	0.50	500	3.00	160
	1960	19	0.60	500	3.50	170
	1970	19	0.70	500	3.75	175
	1975	19	0.75	500	4.00	185
	1980	19	0.80	500	4.50	190
	1910	19	1.00	1000	12.00	240
	Friction Seal Strap (without embossing)	Manual 1160	11	0.60	1000	6.00
Manual 1580		15	0.80	1000	9.50	245
Manual 1590		15	0.90	1000	10.00	260
Machine 1160		11	0.60	2000	12.00	160

Customized options are also available. Contents are subject to change without notice.

WE ARE OFFERING WIDE RANGE OF ISO/CE CERTIFIED MANUAL / AUTO / BATTERY & PNEUMATIC OPERATED TOOLS FROM OUR ASSOCIATES WITH COMPLETE SERVICE SUPPORT AND AVAILABILITY OF SPARES / TECHNICAL ASSISTANCE. THE DETAILS ARE ENCLOSING HEREWITH.

PET SPECIFICATION

USE TYPE	Product Polyethylene Terephthalate Strapping				Length Average/ Meterage ± 5%	Average Net Wt (Kgs) ± 100 gm	Average Strength (± 5% Kgs)
	Code	Width (± :0.3 mm)	Thickness (± : 0.03 mm)	Plain / Emb.			
Suitable for all high production 1. Fully Automatic power strapping machines 2. Pneumatic Manual Tools 3. Battery Operated Manual Tools 4. Manual Sealer & Tensor Standard Core Sizes- 406 ID X 150 L x 1.2 kg. 203 ID X 165 L x 800 gram or as required. Packing- 1 roll in one paper sheet / carton.	06060	6	0.60	Emb.	4280	20.00	140
				Plain	4150	20.00	150
	09060	9	0.60	Emb.	2850	20.00	210
				Plain	2770	20.00	220
	10060	10	0.60	Emb.	2570	20.00	230
				Plain	2490	20.00	240
	11050	11	0.50	Emb.	2800	20.00	210
				Plain	2720	20.00	220
	11060	11	0.60	Emb.	2330	20.00	260
				Plain	2260	20.00	270
	11070	11	0.70	Emb.	2000	20.00	300
				Plain	1940	20.00	310
	12050	12	0.50	Emb.	2570	20.00	230
				Plain	2490	20.00	240
	12060	12	0.60	Emb.	2140	20.00	280
				Plain	2080	20.00	290
	12070	12	0.70	Emb.	1830	20.00	330
				Plain	1780	20.00	340
	12080	12	0.80	Emb.	1600	20.00	370
				Plain	1560	20.00	390
	13060	13	0.60	Emb.	1980	20.00	300
				Plain	1920	20.00	320
	13070	13	0.70	Emb.	1690	20.00	350
				Plain	1640	20.00	370
	14060	14	0.60	Emb.	1830	20.00	330
				Plain	1780	20.00	340
	15060	15	0.60	Emb.	1710	20.00	350
				Plain	1660	20.00	360
	15070	15	0.70	Emb.	1470	20.00	410
				Plain	1420	20.00	420
	15080	15	0.80	Emb.	1290	20.00	470
				Plain	1250	20.00	500
	15090	15	0.90	Emb.	1140	20.00	530
				Plain	1100	20.00	540
	16070	16	0.70	Emb.	1380	20.00	440
				Plain	1340	20.00	450
	16090	16	0.90	Emb.	1070	20.00	560
				Plain	1040	20.00	580
	16100	16	1.00	Emb.	960	20.00	620
				Plain	930	20.00	640
	17080	17	0.80	Emb.	1130	20.00	530
				Plain	1100	20.00	550
17090	17	0.90	Emb.	1010	20.00	600	
			Plain	980	20.00	620	
18080	18	0.80	Emb.	1070	20.00	560	
			Plain	1040	20.00	580	
18090	18	0.90	Emb.	950	20.00	630	
			Plain	920	20.00	650	
18100	18	1.00	Emb.	860	20.00	700	
			Plain	830	20.00	720	
19080	19	0.80	Emb.	1020	20.00	590	
			Plain	980	20.00	610	
19100	19	1.00	Emb.	810	20.00	740	
			Plain	790	20.00	760	
19127	19	1.27	Emb.	640	20.00	940	
			Plain	620	20.00	970	

Customized options are also available. Contents are subject to change without notice.

WE ARE OFFERING WIDE RANGE OF ISO/CE CERTIFIED MANUAL / AUTO / BATTERY & PNEUMATIC OPERATED TOOLS FROM OUR ASSOCIATES WITH COMPLETE SERVICE SUPPORT AND AVAILABILITY OF SPARES / TECHNICAL ASSISTENCE. THE DETAILS ARE ENCLOSING HEREWITH.



Suitable for the strap width of **13-16-19 mm X 1.3 mm**. Required air pressure 5 Kg/sq.cm to 6.5Kg/sq.cm (max) and maximum achievable Tension is **3000 N**. Friction / vibration sealing system . Weight: 3.8 Kg. Different models are available for 25 mm width strap as well as Bailing Application model (only sealing)

Pneumatic Heavy Duty PET / PP Strapping Tools



Suitable for strap width of **16 mm to 19 mm X 0.8mm to 1.3 mm**. Required air pressure 5.5 Kg/sq.cm to 6.5 kg/sq.cm and maximum achievable tension is **5000 N. Max**. Tension speed 6 Mtr/ min or 20 Ft/min. Friction / vibration sealing system. Euro standard safety feature. Weight: 5.3 Kg.

Battery Operated Digital programmable PET / PP Strapping Tools



Battery operated Heavy Duty model with new DIGITAL ADJUSTMENT facility of Tension and Sealing time. Different models suitable for **16 mm to 19 mm X 1.3 mm (1 mm for PP) and 10 mm to 16 mm X 1 mm** width of strap. Wide range of Models are available with **3400 N / 2300 N & 2000 N** Tension force to meet different range of strapping application. Easy operate and low maintenance cost. Euro standard safety features with unique design and world's most advance strapping technology. Special model for Bailing Application (only sealing).

Manual PET Strapping Cutter



INDPACK make Manual PET strapping cutter. More specification, please visit to the Strap Cutter Menu.